

# Product Bulletin

**Concept® 106**

## TRANSPARENCY MOUNTING FILM

Concept® Transparency Mounting Film is a double-coated pressure sensitive 1.0 mil polyester film with the optically clear 204-4100 permanent acrylic adhesive. Two 1.5 mil polyester film liners are used to maintain excellent adhesive clarity. This clear mounting film offers protection from UV, abrasion, moisture and other environmental exposures. This product is designed for laminating thin flexible films and papers under 10 mils in total thickness. It can be laminated by the cold laminating process without the addition of heat.

### Applications

Transparency Mounting Film is designed to mount backlit transparencies to glass, Plexiglas® or other clear substrates in light box applications. The product also provides distortion-free face mounting of prints to these same clear substrates.

### Thickness

Film	1.0 mils.
Adhesive	1.3 to 1.7 mils each side.
Liner	1.5 mils.
(Thickness variance +/- 10%)	

### Dimensional Stability

Good.

### Expected Exterior Exposure

Up to 1 year under normal exposure conditions

### Temperature Ranges

Minimum application temperature	+40° F.
Service temperature range	-40°F to +200°F.

### Adhesion

To stainless steel	48 oz/in.
--------------------	-----------

When tested according to PSTC-1 01 Method A with 24 hr. dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.

### Light Transmission

Approximately 84% @ 550nms.

### Storage Stability

1-year shelf life when stored at 70°F and 50% relative humidity.

### Product Series

106-31 31" x 150'  
106-38 38" x 150'  
106-51 51" x 150'  
106-54 54" x 150'



***Manufacturer of Pressure Sensitive Films,  
Traffic Graffice Floor Advertising Films,  
Custom Coatings and Printing Inks.***

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537  
Web Site: [www.generalformulations.com](http://www.generalformulations.com) • e-mail: [gfiinfo@generalformulations.com](mailto:gfiinfo@generalformulations.com)

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.