Product Bulletin

Concept® 101 LUSTRE OVERLAMINATING FILM

Concept® Lustre Overlaminating Film 101 is a pressure sensitive 3-mil lustre PVC film with a clear 200-4990 permanent acrylic adhesive on a smooth paper liner. This vinyl film offers protection from abrasion, moisture and other environmental exposures. It is laminated by the cold laminating process without the addition of heat.

Applications Lustre overlaminating film is designed to protect digital image prints and screen printed

images for exhibit and display graphics. Can be used in most instances where an overlay

with a semi-gloss finish is required.

Thickness Film 3.0 mils.

Adhesive .8 to 1.0 mil. Liner 4.0 mils. (Thickness variance +/- 10%)

Dimensional Stability Good.

Temperature Ranges Minimum application temperature +40° F

Service temperature range -40°F to +180°F.

Expected Exterior Exposure This product is designed for interior applications.

Exterior resistance has not been determined.

Adhesion To stainless steel 48 oz/in.

Tested according to PSTC-101 Method A procedures.

24 hr. dwell at 70°F and 50% relative humidity.

Typical values. Individual values may vary. Test thoroughly before production.

Light Transmission Approximately 87%

Gloss

60° Gardner-MD Initial 30-50

Storage Stability 1-year shelf life when stored at 70°F and 50% relative humidity.

Product Series 101-31 (31" x 150' roll)

101-39 (38" x 150' roll) 101-52 (51" x 150' roll) 101-55 (54" x 150' roll) 101-61 (61" x 150' roll)



Manufacturer of Pressure Sensitive Films, Traffic Graffic Floor Advertising Films, Custom Coatings and Printing Inks.

309 S. Union ● P.O. Box 158 ● Sparta, Michigan 49345 ● (616) 887-7387 ● (800)253-3664 ● FAX (616)887-0537 Web Site: www.generalformulations.com ● e-mail: gfiinfo@generalformulations.com